

Package: opensky (via r-universe)

November 2, 2024

Title Templates for 'ggplot2' and 'R Markdown'

Version 0.2.0

Description Templates for 'ggplot2' and 'R Markdown'. 'opensky' provides functions to include templates for 'xaringan' slides, 'ggplot2' helpers, and 'R Markdown' documents.

License MIT + file LICENSE

URL <https://github.com/emptyfield-ds/opensky>

BugReports <https://github.com/emptyfield-ds/opensky/issues>

Imports fs, rlang, usethis (>= 2.1.0)

Suggests covr, mockr, testthat (>= 3.1.0), withr

Remotes malcolmbarratt/testthat@snapshot_file_path

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

Repository <https://emptyfield-ds.r-universe.dev>

RemoteUrl <https://github.com/emptyfield-ds/opensky>

RemoteRef HEAD

RemoteSha f9e1864986084933a1965bb4e646ea431267ae7d

Contents

use_blank_rmd	2
use_ggplot2_utils	2
use_purrr_compat	3
use_r_hub	3
use_testthat_setup	4
use_utils	4
use_xaringan_kakashi	5

Index	6
--------------	----------

use_blank_rmd	<i>Use a blank R Markdown file with reasonable settings</i>
---------------	---

Description

Use a blank R Markdown file with reasonable settings

Usage

```
use_blank_rmd(save_as, open = is_interactive())
```

Arguments

save_as	Path of file to create, relative to root of active project. Defaults to <code>template</code>
open	Open the newly created file for editing? Happens in RStudio, if applicable, or via <code>utils::file.edit()</code> otherwise.

use_ggplot2_utils	<i>Use ggplot2 templates</i>
-------------------	------------------------------

Description

Including `theme_minimal2()`, `geom_point2()`, and other variants

Usage

```
use_ggplot2_utils(save_as = NULL, open = FALSE)
```

Arguments

save_as	Path of file to create, relative to root of active project. Defaults to <code>template</code>
open	Open the newly created file for editing? Happens in RStudio, if applicable, or via <code>utils::file.edit()</code> otherwise.

use_purrr_compat	<i>Use compat-purrr.R from rlang</i>
------------------	--------------------------------------

Description

Use compat-purrr.R from rlang

Usage

```
use_purrr_compat(save_as = "compat-purrr.R", open = is_interactive())
```

Arguments

save_as	Path of file to create, relative to root of active project. Defaults to <code>template</code>
open	Open the newly created file for editing? Happens in RStudio, if applicable, or via <code>utils::file.edit()</code> otherwise.

use_r_hub	<i>Use an ignored rhub.R file</i>
-----------	-----------------------------------

Description

Use an ignored rhub.R file

Usage

```
use_r_hub(save_as = "rhub.R", open = is_interactive())
```

Arguments

save_as	Path of file to create, relative to root of active project. Defaults to <code>template</code>
open	Open the newly created file for editing? Happens in RStudio, if applicable, or via <code>utils::file.edit()</code> otherwise.

use_testthat_setup *Create setup.R in the testthat file*

Description

Create setup.R in the testthat file

Usage

```
use_testthat_setup(open = is_interactive())
```

Arguments

open Open the newly created file for editing? Happens in RStudio, if applicable, or via `utils::file.edit()` otherwise.

use_utils *Use utils.R with %||% and %nin%*

Description

Use utils.R with %||% and %nin%

Usage

```
use_utils(save_as = "utils.R", open = is_interactive())
```

```
edit_utils(open = is_interactive())
```

Arguments

save_as Path of file to create, relative to root of active project. Defaults to `template`

open Open the newly created file for editing? Happens in RStudio, if applicable, or via `utils::file.edit()` otherwise.

use_xaringan_kakashi *Use xaringan templates*

Description

Use xaringan templates

Usage

```
use_xaringan_kakashi(save_as, open = is_interactive())
```

```
use_xaringan_tozan(save_as, open = is_interactive())
```

Arguments

save_as	Path of file to create, relative to root of active project. Defaults to <code>template</code>
open	Open the newly created file for editing? Happens in RStudio, if applicable, or via <code>utils::file.edit()</code> otherwise.

Index

`edit_utils` (`use_utils`), 4

`use_blank_rmd`, 2

`use_ggplot2_utils`, 2

`use_purrr_compat`, 3

`use_r_hub`, 3

`use_testthat_setup`, 4

`use_utils`, 4

`use_xaringan_kakashi`, 5

`use_xaringan_tozan`
 (`use_xaringan_kakashi`), 5

`utils::file.edit()`, 2–5